Fortus 450mc



Industrial FDM technology with an open material ecosystem for advanced prototyping, tool production and end-use parts.

Bring the speed, agility and design freedom of advanced additive manufacturing to your business while gaining the latest advances in FDM® technology. The Fortus 450mc^{TM} 3D printer builds high-requirement functional prototypes, rugged manufacturing tooling and custom production parts in its large $406 \times 355 \times 406 \text{ mm}$ ($16 \times 14 \times 16 \text{ in.}$) build envelope. Fourteen Stratasys Preferred Materials, multiple Stratasys Validated Materials and soluble support address a wide variety of applications.

OpenAM™ software lets users alter print parameters to optimize material capabilities and print results. GrabCAD Print™, GrabCAD Print Pro™, and Insight™ software provide an easy CAD-to-print workflow and in-depth print processing control. MTConnect and Stratasys Software Development Kits let you integrate the Fortus 450mc into your connected factory floor.

System Specifications				
Build Envelope (XYZ)	406 x 355 x 406 mm (16 x 14 x 16 in.)			
Material Delivery	Two bays each for model and support canisters. Auto changeover between canisters			

Product Specifications						
System Size and Weight	129.5 cm x 90.2 cm x 198.4 cm (51 x 35.5 x 78.1 in.) 601 kg (1325 lbs.)					
Achievable Accuracy	Parts are produced within an accuracy of ± .127 mm (± .005 in.) or ± .0015 mm/mm (± .0015 in/in), whichever is greater). Z part accuracy includes an additional tolerance of -0.000/+slice height. Note: Accuracy is geometry dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield.					
Network Communication	10/100 base T connection. Ethernet protocol. Wired: TCP/IPv6 protocols					
Operator Attendance	Limited attendance for job start and stop required					
Power Requirements	208VAC 3 phase, 50/60 Hz, consumes 18 Amps					
Regulatory Compliance	CE, cTUVus, RCM, EAC, FCC Part B					
Software	All Fortus systems include Insight™ and Control Center™ job processing and management software. Compatible with GrabCAD Print™ and GrabCAD Print Pro™ for use with part processing, job reports, scheduling and remote monitoring. OpenAM software is available through the purchase of an OpenAM License.					
Operating System	Insight: Microsoft Windows 11, Microsoft Windows 10, or Microsoft Windows Server 2012 R2 GrabCAD Print, GrabCAD Print Pro, and OpenAM: Windows 10 and newer, Windows Server 2016 and newer. Only 64-bit versions of Windows are supported.					

Material Options										
Stratasys Preferred Materials										
Material	Layer Thic 0.127 mm (0.005 in.)	kness 0.178 mm (0.007 in.)	0.254 mm (0.010 in.)	0.330 mm (0.013 in.)	Support Structure	Available Colors				
ABS-ESD7™	0	•	•	0	Soluble	■ Black				
ABS-M30™	•	•	•	•	Soluble	Ivory■ Black■ Blue	□ White ■ Red ■ Dark Gray			
ABS-M30i™	•	•	•	•	Soluble	Ivory				
Antero™ 800NA	0	0	•	0	Breakaway	Natural				
Antero 840CN03	0	0		0	Breakaway	Natural				
ASA	•	•	•	•	Soluble	■ Black ■ Dark Gray ■ Light Gray □ White ■ Ivory	Dark BlueGreenYellowOrangeRed			
FDM Nylon 12™	0	•	•	•	Soluble	■ Black				
FDM Nylon 12CF™	0	0	•	0	Soluble	■ Black				
PC		•	•	•	Breakaway, Soluble	□ White				
PC-ABS	•	•	•	•	Soluble	■ Black				
PC-ISO™	0	•	•	•	Breakaway	Translucent Natural	☐ White			
ULTEM™ 9085 resin	0	0	•	•	Breakaway	■ Tan	■ Black			
ULTEM™ 1010 resin	0	0	•	•	Breakaway	Natural				
ST-130	0	0	0	•	Breakaway	■ Tan				

Stratasys Validated Materials							
Material	Layer Thickness 0.127 mm 0.178 mm 0.254 mm 0.330 mm (0.005 in.) (0.007 in.) (0.010 in.) (0.013 in.)				Support Structure	Available Colors	
FDM HIPS	0	0	•	0	Breakaway	■ Light Gray	
Kimya PC-FR	0	0	•	0	Soluble	■ Light Gray	
ULTEM® 9085 Resin (colors)	0	0	•		Breakaway	■ Red	
	0	0	•	0	Breakaway	Jana White	
	0	0		0	Breakaway	Dream Gray	
	\circ	\circ		\circ	Breakaway	□ White 7362	
	0	0	•	0	Breakaway	■ Gunship Gray	
	0	0	•		Breakaway	■ Aircraft Gray	
PC	0	0	•	0	Soluble	■ Red ■ Black	
PC-ABS	0	0	•	0	Soluble	■ Red	
VICTREX AM™ 200	0	0	•	0	Breakaway, Soluble	■ Natural	
PC-ESD	0	0	•	0	Soluble	■ Black	



stratasys.com ISO 9001:2015 Certified Stratasys Headquarters

7665 Commerce Way, Eden Prairie, MN 55344

- +1 800 801 6491 (US Toll Free)
- +1 952 937-3000 (Intl)
- +1 952 937-0070 (Fax)

1 Holtzman St., Science Park, PO Box 2496 Rehovot 76124, Israel +972 74 745 4000 +972 74 745 5000 (Fax)

PRODUCT SPEC SHEET FDM

© 2024 Stratasys. All rights reserved. Stratasys, the Stratasys Signet logo, FDM, and Fortus are registered trademarks of Stratasys Inc. Fortus 450mc, ABSi, ABS-M30, ABS-ESD7, Antero 800NA, Antero 840CN03, PC-ISO, FDM Nylon 12, FDM Nylon 12CF, Insight, Control Center, GrabCAD Print, GrabCAD Print Pro, and OpenAM are trademarks of Stratasys, Inc. 9085, 1010 and ULTEM™ are trademarks of SABIC, its affiliates or subsidiaries. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. Product specifications subject to change without notice. PSS_FDM_Fortus450mc_0924a